


EXPERTS IN PLUG & PLAY LED TUBES, LED HIGH BAYS AND LED IN CEILING SPECIALIST

- ✔ Housing made of high-quality machined aluminum.
- ✔ Round & square design, available in five different diameters.
- ✔ LED SMD board designed specifically for solo LED.
- ✔ LED module can be replaced on site.
- ✔ Perfect uniform spread of light across the diffuser.
- ✔ Built in high efficient driver.
- ✔ Dimmable & Non-dimmable for option.



SPECIFICATION

SKY LSSMM061-E

Item No:		LSSMM061-E				
Product Category		LED Suspension downlight				
Installation		Suspension				
IP Grade		IP 20				
Beam Angle		N/A				
Power Consumption		Max.215W				
Dimension		D1200*H70mm				
Cut out		N/A				
Ambient Temperature		-20°C~45°C				
Finishing Color		WH/BK				
Optical Parameters						
LED Source		Osram				
Lamp Life		35000-5000H				
Luminance uniformity		≥0.9				
Color Shift		≤0.004				
Center intensity						
Clour Temperature	Initial Lumen	Lumen Efficiency	CRI	Chromaticity Coordinates	Color Difference	
3000K	19350lm	90lm/W	90	N/A	≤3	
Power Model		Osram				
Energy Grade		1				
Dimmable		N/A				
Power factor		≥0.9				
Input Voltage		220-240V				
Output Voltage		1200mA 30-40Vd.c.				
Input Current Frequency		50Hz/60Hz				
Others:						
Safety	CE/Rohs					
Warranty	5 years					

