

**EXPERTS IN PLUG & PLAY LED TUBES, LED HIGH BAYS AND LED IN CEILING SPECIALIST**

- ✔ LED fixture for wall installation for direct / indirect emission.
- ✔ Die-casting body, powder coated with white, or black finishes.
- ✔ Complete with mounting bracket in stainless steel.
- ✔ Optic accessories it is possible to create scenographic lighting effects on the surface to be illuminated and to trim the light beams according to specific project requirements.
- ✔ 3000k/4000K is available with Ra80, Ra90.



**SPECIFICATION**

**ARM LSSMM084-A**

<b>Item No:</b>		<b>LSSMM084-A</b>		
Product Category		Wall lamp		
Installation				
IP Grade		IP 20		
Beam Angle				
Power Consumption		9W		
Dimension		L300*W77*H37		
Cut out		/		
Ambient Temperature		-20 °C~45 °C		
Finishing Color		WH/BK		
Optical Parameters				
LED Source		CREE		
Lamp Life		35000-50000H		
<b>Center intensity</b>				
Clour Temperature	Initial Lumen	Lumen Efficiency	CRI	Color Differenc e
3000/4000	720lm	80lm/w	>80	≤ 3 steps
Power Model		EOE		
Dimmable		Dimmable/Non-dimmable		
Input Voltage		220-240V		
Input Current Frequency		50HZ / 60HZ		
Output Voltage		37V		
Output Current		200ma		
Power factor		≥0.9		
Others:				
Safety	CE/Rohs			
Warranty	5 years			

